

INTRODUCTION

Polyurethane KP- Top Coat is 2 components high-performance top coating paint for Polyurethane. Polyurethane KP- Top Coat has strong adhesive properties, weather proof function, chemical resistance. Polyurethane KP- Top Coat special properties can protect Poly Urethane and Poly Urea layer against external environment

FEATURES

- Quick dry and easy apply.
- Weatherproof, chemical resistance, durable properties.
- High adhesive performance with Poly Urethane and Poly Urea.

USAGE

Top coat for Poly Urethane and Poly Urea

COLOR & PACKING

- General color: Green and Grey
- Customized color: Blue, White, Blown etc
- Packing: 15Kg(Hardener), 3Kg(Main)

THEORETICAL COVERAGE

0.3 Kg / m² (Based on 1m²)

FEATURES

Appearance	Hardener: Grey, Green Main: Yellowish Liquid
Viscosity (KU/25°C)	Hardener: 70 ~ 80 KU Main: 45 ~ 55 KU
Specific gravity	Hardener: 1.15 ~ 1.25 Main: 0.98 ~ 1.05
Mixing ratio	Hardener : Main = 5:1
Pot life (hrs)	2h ~ 3h
Curing Time (hrs)	5h

STORAGE

- Use within six (6) months after manufacturing date written on the label.
- Store in cool, dry and well-ventilated place (Store temperature: 5-35°C).
- Avoid exposure to humidity and UV.
- Keep away product from heat, spark and flames.

APPLICATION

1. Surface Treatment

- Remove oil, water, dust on the exist surface, completely.
- Surface must be well cured.
- Use product with below condition.
 - Weather temperature: 5-35°C
 - Surface temperature: below 40°C
 - Relative Humidity: below 80%
 - Moisture content on concrete: below 6%

2. Application method

- Mix Polyurethane KP- Top Coat at least 5 min.
- Apply product evenly with brush or roller or spray machine within curing time. (Thickness must be over 0.04mm)

NHÀ PHÂN PHỐI

CÔNG TY TNHH XD - TM KOMIX

Số 87 Đường D1, Khu Đô Thị Mới Him Lam, P. Tân Hưng, Quận 7, TP. HCM
ĐT: (84-8) 6271 0066/77 - Fax: (84-8) 6251 5718

WEBSITE

www.komixvietnam.vn
www.chongthamkomix.vn
www.thegioichongtham.vn